

SCHUTZ™ Door Release Exit Switches

SCHUTZ door release exit switch is an integral part of all access control system. The doors are secured and simultaneously offers easy exits. These exit push switches are available in single pole, double pole and with tamper variants however model differs. It is 12/24VDC operated (must be the same voltage of ACS) flush mount device.

PUSH TO EXIT BUTTON SWITCHES

MODEL Number	IPTEB-33SS	IPTEB-33AA	IPTEB-33SS-L
Product Image			
Contact Rating	3A@125–250VAC	3A@125–250VAC	3A@125–250VAC
Actuator Type	Spring Return - Momentary	Spring Return - Momentary	Spring Return - Momentary
Output Contacts	NO/COM	NO/COM	NO/COM
Finish	MATT	Sandblast	MATT
Face Plate	SS 304	Aluminium Alloy	SS 304
Dimensions (mm)	86(W)*86(H)*25(D)	86(W)*86(H)*25(D)	86(W)*86(H)*25(D)

MUSHROOM HEAD SWITCHES

MODEL Number	IPTEM-01G	IPTEM-03G	IPTEM-04R
Product Image			
Contact Rating	3A@250VAC	3A@125–250VAC	3A@125–250VAC
Actuator Type	Spring Return - Momentary	Spring Return - Momentary	Spring Return - Momentary
Output Contacts	NO/NC/2COM	NO/NC/COM	NO/NC/COM
Push Button Size	22mm Dia	32mm Dia	32mm Dia
Material	SS 304	SS 304	SS 304
Dimensions (mm)	86(W)*86(H)*25(D)	86(W)*86(H)*25(D)	86(W)*86(H)*25(D)

NO TOUCH EXIT SENSORS

MODEL Number	IIRDR-02SS	IIRDR-01SS	IIRDR-86WP (Outdoor)
Product Image			
Operating Voltage	12V DC	12V DC	12V DC
Contact Rating	1A@30VDC	1A@30VDC	1A@30VDC
Output Contacts	NO/NC/COM	NO/NC/COM	NO/NC/COM
Sensing Range	0.1 – 10 Cm	0.1 – 10 Cm	5 – 20 Cm
Face Plate	SS 304	SS 304	SS 304
Dimensions (mm)	86(W)*86(H)*25(D)	86(W)*86(H)*25(D)	86(W)*86(H)*25(D)

KEY OVERRIDE SWITCHES

MODEL Number	IKOS-33	IKOS-33-L	IKOS-33-LT
Product Image			
Contact Rating	3A@250VAC	3A@250VAC	3A@250VAC
Operating Voltage	12V DC	12V DC	12V DC
Output Contacts	NO/NC/COM	NO/NC/COM+LED	NO/NC/COM+LED+Tamper
Face Plate	SS 304	SS 304	SS 304
Dimensions (mm)	86(W)*86(H)*30(D)	86(W)*86(H)*30(D)	86(W)*86(H)*30(D)

PANIC SWITCHES

MODEL Number	IPTEM-02R(K)	IPBK-86ABS	IKOS-33-LT
Product Image			
Contact Rating	5A@250VAC	3A@250VAC	1A@30VDC
Actuator Type	Latching – Dual Action	Latching – Dual Action	Latching – Dual Action
Output Contacts	1NO + 1NC	NO/NC/COM	NO/NC/COM
Reset	Rotate / Key to reset	Key	Key
Face Plate	SS 304	ABS	Polystyrene
Dimensions (mm)	86(W)*86(H)*38(D)	86(W)*86(H)*32(D)	53(W)*70(H)*27(D)

PLASTIC SWITCHES

MODEL Number	IPTEB-33ABS	IPTEB-EM	CQR-HUSH2
Product Image			
Operating Voltage	12V / 24VDC	12V / 24VDC	12V DC
Contact Rating	3A@250VAC	3A@36VDC	3A@36VDC
Actuator Type	Momentary	Momentary	Latching – Dual Action
Output Contacts	NO/NC/COM	NO/COM	NO/NC/COM + 2Tamper
Material	ABS	ABS	ABS
Dimensions (mm)	86(W)*86(H)*20(D)	23(W)*76(H)*14(D)	46(W)*72(H)*20(D)

Disclaimer: SCHUTZ reserves the right to go ahead with any modifications of products or prices without notice. All the information and specifications stated in this document are current at the time of publication.

